

MT2E SERIES

# LS Tractor



MT230E / MT235E / MT235HE / MT240E / MT240HE  
VALUE COMPACT TRACTORS

6-YEAR LIMITED WARRANTY. SEE DEALER FOR DETAILS



# MT2E SERIES

VALUE COMPACT TRACTORS


## RECOMMENDED IMPLEMENTS/ ATTACHMENTS



**LOADER:**  
High Capacity With  
An Abundance Of  
Standard Features



**BACKHOE:**  
Excellent Capacity,  
Smooth And  
Consistent Operation  
For Added Control



**ROTARY CUTTER:**  
Durable Heavy Steel  
Design Providing  
Quality And Strength



**BOX BLADE:**  
Features A Heavy  
Welded Steel  
Design For Use In  
Demanding Applications

## FEATURES

- *6 Year Warranty\**
- *Available In 30 HP, 35 HP And 40 HP*
- *3 Range Hydrostatic Transmission (2 Pedal)*
- *F12xR12 Synchro Shuttle Gear Drive Models*
- *High Capacity And Performance*



**Ergonomically Located And  
Designed Joystick**  
Provides Comfortable Access  
For Loader Operations. 3<sup>rd</sup>  
Function (Option)



**3 Range Hydrostatic  
Transmission**  
(2 Pedal) Comfortable And  
Efficient Operator Control



**Electronic Engagement PTO**  
Convenient Location




**Standard Factory Grille  
Guard W/ Loader**  
Full Length Grille Guard  
Protects Body Panels  
And Radiator



**Synchro Shuttle Shift  
Transmission**  
Easily Transition From  
Forward To Reverse



**Rubber Platform  
Matting And Step**  
Provide Added Comfort And  
Access To The Spacious  
Operator's Platform



**High Capacity Three Point**  
Lifts Up To 1,808 lbs.



**Standard Foldable ROPS**  
Enables Easy Adjustment  
For Clearance



**Skid Steer Quick Connect  
Loader/Bucket**  
Transition Between Front  
Attachments Quickly



MT230E / MT235E / MT235HE / MT240E / MT240HE



SPECIFICATIONS

CATEGORY					
ENGINE	MT230E	MT235E	MT235HE	MT240E	MT240HE
Type	3 Cylinder, Liquid-cooled, Diesel, NA, CRDI			3 Cylinder, Liquid-cooled, Diesel, TC, CRDI	
Model (Tier 4)	L3C19-D3	L3C19-D2		L3C19-T4	
Engine HP (gross)	30	35		40	
PTO (HP)	25.5	29.7	28	34	32
Rated Speed (rpm)	2,600				
Displacement (in³.)	114.7				
Fuel Tank Capacity (gal.)	7.4				
Alternator (V-A)	12 - 70				
DRIVE TRAIN					
Transmission	Synchro Shuttle	Synchro Shuttle	HST	Synchro Shuttle	HST
No. Of Speed	F12 X R12	F12 X R12	3 Ranges	F12 x R12	3 Ranges
Brakes	Wet, Multi-disc				
PTO					
Type	Independent				
Rear (rpm)	540 (Standard)				
Mid (rpm)	2,000 (Option)				
HYDRAULIC SYSTEM					
Control System	Position				
Implement Pump (gpm)	8.2				
Steering Pump (gpm)	4.1	4.1	5.5	4.1	5.5
Steering	Hydrostatic Power Steering				
Total Flow (gpm)	12.3	12.3	13.7	12.3	13.7
Category (3pt Hitch)	CAT I				
Hitch Lift Capacity (Hitch End) (lbs.)	1,808				
Remote Valves	Option				
DIMENSION					
Overall Length (Frame To Link, in.)	121				
Overall Width With Tires (in.)	54				
Wheelbase (in.)	69				
Height To Top Of ROPS (in.)	88				
TIRE SIZE					
Front / Rear Ag	7 - 14 / 11.2 - 24				
Front / Rear Industrial	25 x 8.5 - 14 / 43 x 16-20				
Front / Rear Turf	25 x 8.5 - 14 / 41 x 14 -20				
WEIGHT					
Total Weight w/o Ballast (lbs.)	2,866	2,866	2,870	2,881	2,884

*\*All Specs and features are subject to change, and pictures could include optional equipment etc.*

FRONT END LOADER	LL3301	LL3302
TRACTOR APPLICATION	MT230E/ MT235E/MT235HE	MT240E/ MT240HE
Bucket Size (in.)	66	
Maximum Lift Height (in.)	94	
Clearance With Attachment Dump (in.)	65.6	
Reach At Maximum Height (in.)	11.5	
Maximum Dump Angle (deg.)	57	
Maximum Rollback Angle (deg.)	40	
Digging Depth (in.)	5.5	
Overall Height In Carry Position (in.)	53	
Lift Capacity (At Pivot Pin) (lbs.)	1,688	2,153
Breakout Force (At Pivot Pin) (lbs.)	2,855	3,579
Approx. Weight (Loader w/o Bucket) (lbs.)	650	653

BACKHOE	LB1105
TRACTOR APPLICATION	MT230E/MT235E/MT235HE/ MT240E/MT240HE
Digging Depth (in.)	76.3
Reach From Centerline Of Swing Pivot (in.)	113.1
Loading Height (in.)	63.6
Swing Arc (deg.)	180
Transport Height (in.)	77.2
Bucket Rotating (deg.)	180
Stabilizer Spread (Down Position) (in.)	68.7
Stabilizer Spread (Up Position) (in.)	46.4
Bucket Digging Force (lbs.)	2,817

SNOW BLOWER	LW3163B	LW3174B
TRACTOR APPLICATION	ALL MT2E SERIES	MT240E/MT240HE
Overall Width (in.)	68	74
Cutting Width (in.)	63, (68 w/Extension)	74
Cutting Height (in.)	23	26
Impeller Drive	Gear Box	
Auger Drive	Worm Gear	Chain Drive
Auger Diameter (in.)	13 3/4	14 3/4
Impeller Diameter (in.)	17 5/8	23 3/4
Number Of Blades On Impeller	4	
Chute Rotation	Hydraulic	
Adjustable Heavy Skid Shoes	Yes	

Additional Equipment

- Standard Factory Toolbox
- Loader/Bucket Indicator Rod
- Platform Step





**LS** Tractor

LS Tractor USA | P: 252.984.0700 | F: 252.984.0701 | [LSTractorUSA.com](http://LSTractorUSA.com)  
(Corporate Address) 6900 Corporation Parkway, Battleboro, NC

