MT2S SERIES

LS Tractor

MT225s

PREMIUM COMPACT TRACTORS

6-YEAR LIMITED WARRANTY. SEE DEALER FOR DETAILS

MT2S SERIES

PREMIUM COMPACT TRACTORS

RECOMMENDED IMPLEMENTS/ ATTACHMENTS

LOADER:
High Capacity With An Abundance Of Standard Features

BACKHOE:
Excellent Capacity, Smooth And Consistent Operation For Added Control

ROTARY CUTTER:
Durable Heavy Steel Design Providing Quality And Strength

BOX BLADE:
Features A Heavy Welded Steel Design For Use In Demanding Applications

FEATURES

- ***6 Year Warranty****
- ***24.7 HP Yanmar Diesel Engine***
- ***3 Range Hydrostatic Transmission (2 Pedal)***
- ***Electric Engagement Independent PTO***
- ***New Heavy-Duty Platform/Frame***

Premium Reversible Seat
Adjustable Foldable Armrest,Tilt High Back Seat. *Reversible Seat Only On Backhoe Models

3 Range Hydrostatic Transmission
(2 Pedal) Comfortable And Efficient Operator Control



Bolted Edge Bucket
Built For The Harshest Conditions

Standard Factory Grille Guard W/ Loader
Full Length Grille Guard Protect Body Panels And Radiator

Optional Thumb Configuration Backhoe
Provides Added Functionality To The Heavy-Duty Backhoe

Optional Drive-Over Mid-Mount Mower Deck
Providing Convenience And Ease Of Adapting To Any Application

Standard Tilt Steering
Provides Enhanced Operator Comfort

Standard Foldable ROPS
Enables Easy Adjustment For Clearance

Mid-Mount Mower Height Adjustment Dial
Enables Precise Height Control Of The Mid-Mount Mower, By A Simple Turn

SPECIFICATIONS

CATEGORY	
ENGINE	MT225s
Type	3 Cylinder-IDI
Model (Tier 4)	3TNV80F-ZXKLST (Yanmar)
Engine HP (gross)	24.7
PTO (HP)	19.3
Rated Speed (rpm)	2,800
Displacement-cu (in^3.)	77.3
Fuel Tank Capacity (gal.)	6.79
Alternator (V-A)	12 - 40
DRIVE TRAIN	
Transmission	HST
No. Of Speed	3 Ranges
Brakes	Wet, Multi-disc
PTO	
Type	Independent
Rear (rpm)	540
Mid PTO (Option)	2,500
HYDRAULIC SYSTEM	
Lift Control System	Position
Implement Pump (gpm)	5.6
Steering Pump (gpm)	3.7
Steering	Hydrostatic Power Steering
Total Flow (gpm)	9.3
Category (3pt Hitch)	CAT I
Hitch Lift Capacity (lbs.) (Hitch End)	1,896
Remote Valves	1 Pair (Option)
DIMENSION (with R1 tires)	
Overall Length (Frame To Link in.)	111.9
Overall Width With Tires (in.)	48.7
Wheelbase (in.)	63.4
Height To Top Of ROPS (in.)	86.4
TIRE SIZE	
Front / Rear Ag (R1)	7 - 12 / 11.2 -16
Front / Rear Industrial (R4)	23 x 8.5 - 12 / 12 - 16.5
Front / Rear Turf (R3)	22 x 8.5 - 12 / 31 x 15.5 - 15
WEIGHT	
Total Weight w/o Ballast (lbs.)	1,764

All Specs and features are subject to change, and pictures could include optional equipment etc.

FRONT END LOADER	LL2300
TRACTOR APPLICATION	MT225s
Bucket Size (in.)	54.3
Maximum Lift Height (in.)	84.4
Clearance With Attachment Dump (in.)	59.1
Reach At Maximum Height (in.)	17.9
Maximum Dump Angle (deg.)	55
Maximum Rollback Angle (deg.)	40
Digging Depth (in.)	4.5
Overall Heights In Carry Position (in.)	46
Lift Capacity (At Pivot Pin) (lbs.)	1,067
Breakout Force (At Pivot Pin) (lbs.)	2,290
Approx. Weight (Loader w/o Bucket) (lbs.)	708

BACKHOE	LB1300
TRACTOR APPLICATION	MT225s
Digging Depth (in.)	84.9
Reach From Centerline Of Swing Pivot (in.)	113.7
Loading Height (in.)	64.7
Swing Arc (deg.)	180
Transport Height (in.)	73.4
Bucket Rotating (deg.)	177
Stabilizer Spread (Down Position) (in.)	82.2
Stabilizer Spread (Up Position) (in.)	65.4
Bucket Digging Force (lbs.)	3,013

MID MOWER	LM2360
TRACTOR APPLICATION	MT225s
Cutting Width (in.)	60
Cutting Height Range (in.)	1 - 4
Transport Height (in.)	6
Gear Type	Spiral Bevel
Number Of Blades	3
Adjustment Of Cutting Height	Dial
Deck Thickness (in.)	0.15
Total Width (in.)	75.7
Total Length (w/o Linkage)	44.1
Total Height (w/o Linkage)	11.9
Lifting Type	3-Point Upper Link
Total Weight (lbs.)	368

Additional Equipment

- Standard Factory Toolbox
- Standard 12 Volt Power Outlet
- Flat Operator With Rubber Mat
- Standard Factory Platform Step

LS Tractor

LS Tractor USA | P: 252.984.0700 | F: 252.984.0701 | LSTractorUSA.com
(Corporate Address) 6900 Corporation Parkway, Battleboro, NC